SOUTHERN NEVADA BUILDING OFFICIALS REGIONAL STANDARDS

B-115 11-02-05 Pg. 1 of 1

BASEMENT AND BEDROOM EGRESS WINDOW

BASIC REQUIREMENT


EGRESS WINDOW

MINIMUM 20" WIDTH, MINIMUM 24" HIGHT OPENING MINIMUM 5.0 SQUARE FEET OF OPENABLE AREA FOR 1ST FLOOR, TOP OF SILL A MAXIMUM OF 44" ABOVE FINISH FLOOR

CROSS SECTION DEEP WELLS

WINDOW WELL

MINIMUM 36" X 36" MINIMUM 9 SQ.FT. CLEAR FLOOR AREA IF DEEPER THAN 44" LADDER OR STEPS REQUIRED A GUARDRAIL IS NOT REQUIRED UNLESS AN EXIT WAY ADJOINS THE WELL.



IF THE TOP OF THE WINDOW WELL WALL IS MORE THAN 44" ABOVE THE FLOOR OF THE WELL, EITHER LADDER OR STAIR EGRESS IS REQUIRED. THE LADDER OR STAIR MAY ENCROACH A MAXIMUM OF 6" INTO THE REQUIRED CLEAR FLOOR SPACE.

LADDER EGRESS

INSIDE WIDTH AT LEAST 12"
RUNGS NOT MORE THAN 18" ON CENTER
MINIMUM 6" TOE SPACE
PERMANENTLY FIXED
NON-COMBUSTIBLE
SHALL EXTEND TO TOP OF WALL

Clark County
Dept. of Develop. Services
4701 W Russell Rd
Las Vegas NV 89118
(702) 455-3000

Henderson
Bldg & Fire Safety Dept
240 Water St.
Henderson, NV 89015
(702) 267-3650

Las Vegas
Building & Safety Dept.
731 S. 4th Street
Las Vegas, NV 89101
(702) 229-6916

Mesquite
Building Department
10 East Mesquite Blvd.
Mesquite NV 89027
(702) 346-2835

North Las Vegas Building Department 2266 Civic Center Drive N. Las Vegas, NV 89030 (702) 633-1577